


TECHNICAL DATA



CHERRY SEALER WAX CNC

A PERFUMED HOT SPRAY WAX FOR AUTOMATIC AND SELF SERVE CAR WASHES.

CHERRY SEALER WAX is a liquid wax emulsion for use in the final rinse arch of automatic car washes. It performs exceptionally following the application of a foaming polish wax to provide a water repelling protective wax coating to the vehicles surface. CHERRY SEALER WAX produces rapid beading action which promotes additional dryness to the automobile.

ADVANTAGES

1. Contains anti-corrosive properties which assists in retarding the formation of rust.
2. Mixes readily and quickly with water forming a stable wax emulsion.
3. Assists in the elimination of water spotting.
4. Facilitates faster drying.
5. Safe for all metal surfaces.
6. Effective even in low concentrations.
7. Appeals to customer sense of smell due to cherry fragrance.

APPLICATION

CHERRY SEALER WAX is applied in the final rinse area of the car wash through a spray arch. Dilute concentrated CHERRY SEALER WAX by adding one part concentrate to ten parts water. This mixture should be applied to the vehicle at rate of eight ounces per car for optimum results. For automatic dispensing consult a Mondo Sales representative. The application of CHERRY SEALER WAX is the last stage of car wash process before entering the blowers.

STORAGE

Avoid excessive heat and keep product from freezing.



MATERIAL SAFETY DATA SHEET

Section 1 - Product Identification and Use.

Product Name: Cherry Sealer Wax CNC

Use: Car Wash Spray Wax

Manufacturer:

Mondo Products Company Limited
695 Westney Road South
Unit #1, Ajax, Ontario L1S 6M9
Emergency No. : 1-800-465-5676
Canutec No.: 1-613-996-6666

Supplier:

Same
Business Tel: 905-426-9339

TDG Hazard Classification: Not Regulated

WHIMIS Classification: D2B (Other Toxic Effects)

n/a = Not applicable n/e = Not established

Section 2 - Hazardous Ingredients

Hazardous Ingredients	%w/w	PIN/CAS #	LD 50	LC 50
Quaternary ammonium compounds				
DiCocoalkyl dimethyl chlorides	5-10	61789-77-3	n/e	n/e
Isopropanol	1-5	67-63-0	3600mg/kg oral, rat	16,000ppm/8h
Amines, C14-18:C16-18-Unsat.,ethoxylated	1-5	68155-39-5	n/e	n/e
Synthetic Lubricant	5-10	Proprietary	>15800mg/kg(oral/rat)	>0.9mg/l(rat6hr)

Section 3 - Physical Data

Physical State : Clear Liquid

Appearance / Odour : Red, Cherry Odour

pH : (as supplied) 6.5 - 8.5

Freezing Point (°C) : 0

Vapour Pressure : Same as Water

Solubility In Water: (20°C) : Miscible

Boiling Point (°C) : >100

Coefficient of Water/Oil Distribution : n/e

Evaporation Rate : n/e

Specified Gravity (g/mL) : .97

Vapour Density : Same as Water

Percentage Volatile : >60%

Odour Threshold : (PPM): n/e

Section 4 - Fire and Explosion Data

Flammable [] Yes [X] No

Flash Point (°C) : n/e

Auto Ignition Temp (°C) : n/e

Extinguishing Media : Water [X]; Dry Chemical [X]; Carbon Dioxide [X]; Foam[X]

Special Fire Fighting Procedures : Normal fire fighting procedures may be used.

Hazardous Combustion Products : Irritating and/or toxic fumes and gases may be emitted upon the products combustion. This product may emit oxides of carbon, oxides of nitrogen, and/or low molecular weight hydrocarbons.

Explosive Sensitivity : n/a

Section 5 - Reactivity Data

Stability : Stable [X] Unstable []

Conditions to avoid: none known

Incompatibility (Materials to Avoid) : Strong oxidizers, anionic surfactants.

Hazardous Decomposition Products : n/a

Conditions of Reactivity : n/a

Section 6 - Toxicological Properties

Route of Entry: Eyes, skin, ingestion

Effects of Acute Exposure to Materials: n/e

Eyes: May cause severe irritation

Skin: Contact may cause skin irritation

Ingestion: May cause irritation, nausea and vomiting

Inhalation: Mist may irritate nose, throat and lungs.

Effects of Chronic Exposure to Materials: n/e

Ecological Information:

Toxicity to fish, Invertebrates, Algae, and Sewage bacteria: n/e

Hazard parameters (LC50 or EC50)	High	Medium	Low
Acute Aquatic Toxicity (mg/L)	<=1	>1 and <=100	>100

Section 7 - Preventative Measures

Personal Protective Equipment

Gloves: Impervious Gloves (latex, rubber, polyethylene, vinyl, neoprene).

Eye Protection: Safety glasses

Other: Impervious Clothes (see under gloves).

Footwear: Safety shoes

Respiratory Equipment: None required, if LC50 is not exceeded. Otherwise an approved respirator is advised.

Special Handling Procedures: Avoid contact with skin and eyes.

Ventilation Requirements: Use in well ventilated area.

Incompatibility: None known.

Spill Procedures: Small spills - flush with water. Large spill: collect in appropriate storage containers.

Flush spill area with large volumes of water to chemical sewer.

Waste Disposal: Dispose in accordance with all Local, Provincial and Federal regulations.

Storage Requirements: Store in a cool, dry area, in a closed container. Avoid freezing.

Section 8 - First Aid Measures

Eyes: Flush with plenty of water for at least 15 minutes. Hold eyelids open while rinsing. Contact your physician.

Skin: Wash contaminated area with warm water and soap.

Ingestion: If victim is conscious administer 1-2 glasses of water. Contact a physician.

Inhalation: Remove victim to fresh air.

Section 9 - MSDS Preparation

Sources Used : MSDS, WHIMIS Regs.

Preparation Date : September, 2014

Prepared By: Mondo Products Company Limited
Lab Personal
695 Westney Road South
Unit #1
Ajax, Ontario
L1S 6M9

Business Tel: 905-426-9339

Emergency No.: 1-800-465-5676

Canutec No.: 1-613-996-6666